

Product data sheet



Product	: Ellen Matic Super	Page 1/2
Product group	: automatic draught excluders	
Description	: automatic draught excluder against draught	
Size	: Width 17 mm, Height 35-47 mm.	
Activation	: one sided	
Max. travel	: 12mm	
Max. gap	: 22 mm	
Min. gap	: 3mm	
Cutting Door	: not applicable	
without demounting door		
Mounting	: by screwing side plates	
Application	: DIN R/L applicable	
Material	: aluminium	
Material seal	: PVC	



Product data sheet

Product : Ellen Matic Super **Page 2/2**

Standard Length : 630, 730, 830, 930, 1030, 1130, 1230 mm
Length alternatives : between 350 – 629 mm (not to be cut, special production, single activation)
Length alternatives : > 1230 mm, not applicable
Length alternatives : max. 1230 mm
Required length : Door size +/- 4 mm
To be cut : at one sided activation 100 mm
Fixed lengths : Fixed lengths can not be shortened
Mounting : Groove 14 x 35/47 mm
Mounting plates: : plates are mentioned to be grooved into the side of the door

Accessories: 2 plates and screws to mount.

Specialties : it seals bigger gaps.

By placing Ellenmatic Super under the door, bigger gaps can be overcome.

Door types : Wooden inner and outer doors



Elton BV Postbus 5 NL-9300AA Roden
Tel 0031 (0)50- 5021199 Fax 0031 (0)50 50 14772 E mail ellen@elton.nl