

Product data sheet



| | | |
|--------------------------------|--|-----------------|
| Product | : Ellen Matic Omega | Page 1/2 |
| Product group | : automatic draught excluders | |
| Description | : automatic draught excluder against draught | |
| Size | : Width 10,5 mm, Height 26 mm. | |
| Activation | : one sided | |
| Max. travel | : 12mm | |
| Max. gap | : 10 mm | |
| Min. gap | : 4 mm | |
| Cutting Door | : not applicable | |
| without demounting door | | |
| Mounting | : by screwing wings under the door | |
| Application | : DIN R/L applicable | |
| Material | : aluminium | |
| Material seal | : Silicone | |



Product data sheet

Product : Ellen Matic Omega **Page 2/2**

Standard Length : 630, 730, 830, 930, 1030 mm
Length alternatives : between 300 – 629 mm (not to be cut, special production, single activation)
Length alternatives : 1030 –1230 mm, (without inside soft strip)
Length alternatives : max. 1230 mm
Required length : Door size
To be cut : at one sided activation 100 mm
Fixed lengths : Fixed lengths can not be shortened
Mounting : Groove 11 x 25 mm
Mounting plates : not applicable

Accessories : not applicable

Specialties : not applicable

Door types : Wooden / Aluminium / Steel doors



Elton BV Postbus 5 NL-9300AA Roden
Tel 0031 (0)50- 5021199 Fax 0031 (0)50 50 14772 E mail ellen@elton.nl